

FLECK[®] 3 00 2 v Maryle - 1 --Fring Aleman - phe LTp - A - - L





FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 250 GPM with a backwash of 100 GPM

Backwash capability accommodates softener tanks up to 63" and filter up to 42" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Designed for single or multiple tank systems

OPTIONS

Filter or softener control valves

Downflow co-current or upflow counter-current regeneration

No hard water bypass piston

Brine cam auxiliary switch

Electromechanical timer auxiliary switch

Treated water regeneration

Versatile top or side mount

Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration Environmental protective cover for water resistance, corrosion resistance, and UV stability

MADE IN THE

Time-tested, hydraulically-balanced piston for service and regeneration Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

NXT- Network controller uses onboard communication capabilities to link multiple valves (via off-the-shelf CAT3, CAT5, or better cables) for system types 4,5,6,7,9,and 14

XT- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programing as well as view of diagnostics

Electromechanical Timer- Simple to adjust and easy to service with quick access to all internal components



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.

TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	3" NPTF/BSPF
Cycles	3 or 5

FLOW RATES (50 PSI INLET) - VALVE ALONE

Continuous	250 GPM (56.8 m³/h)
15 psi drop	225 ODM (72 O - 3/b)
Peak 25 psi drop	325 GPM (73.8 m ³ /h)
Cv	65
flow at 1 psi drop	
Max. Backwash	100 GPM (22.7 m ³ /h)
25 psi drop	

REGENERATION

Downflow/Upflow Both A mIIEMC /Span DMCID 109 BDCak



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209 P: 262.238.4400 [] WWW.PENTAIRAQUA.COM [] CUSTOMER CARE: 800.279.9404 [] tech-support@pentair.com